



F-LED

I **CN1:** Connettore alimentazione
12-265Vac~ / Vdc
JP1: On=Luce lampeggiante;
Off=Luce fissa
F1: 250V - 5A
ASSORBIMENTO: 15mA

F **CN1:** Connecteur alimentation
12-265Vac~ / Vdc
JP1: On=Lampe clignotante;
Off=Lumière fixe
F1: 250V - 5A
ABSORPTION: 15mA

E **CN1:** Conector alimentación
12-265Vac~ / Vdc
JP1: On=Luz intermitente;
Off=Luz fija
F1: 250V - 5A
ABSORCIÓN : 15mA

GB **CN1:** Power supply connector
12-265Vac~ / Vdc
JP1: On=Flashing light;
Off=Fix light
F1: 250V - 5A
ABSORPTION: 15mA

D **CN1:** Netzanschluss
12-265Vac~ / Vdc
JP1: On=Blinklampe;
Off=Dauerlicht
F1: 250V - 5A
AUFNAHME: 15mA

I **Nota:** il lampeggiatore deve essere montato esclusivamente in posizione verticale

F **Remarque:** La lampe clignotante doit être montée exclusivement en position verticale

D **Hinweis:** Die Blinklampe darf nur in vertikaler Position montiert werden

GB **Note:** the flashing lamp must be mounted exclusively in vertical position

E **Nota:** la lámpara tiene que ser montada exclusivamente en posición vertical

